



SPECIFICATIONS

Power	100-240V AC 12V DC adaptor Rechargeable battery
Material	Mild steel structure SUS304 S.S. cover and pole
Display	38mm 1.5" LED
Capacity	6/15/30/60/150/200/300/500 kg
Division	1/2/5/10/20/50/100 g
Units	kg/lb
Output	RS232*1
Load Cell	M13/M15/M17
Certification	CE
Load Cell Protection	IP65
Indicator Protection	IP54
Platform Size	300x300mm 300x400mm 400x400mm 400x500mm 500x600mm 600x600mm
Operating Temperature	-10 °C - 40 °C



FUNCTIONS

Counting
(Peak) Hold
Totalization
Animal weighing

FEATURES

- X1 indicator with multi functions
- Large 38mm red LED display
- Default with RS232 interface
- Capacity up to 500kg
- Four anti-slip adjusting feet
- Rubber buffer pan supports
- Overload protection
- kg/lb units exchange

OPTIONAL

Accessories	Part No.
S.S. bracket	109001
Relay 2 output	109002
Relay 4 output	109003
Bluetooth	109004
Bluetooth-(With app)	109005
Ethernet/WiFi	109006
WiFi	109007
RS485	109008
4-20mA	109009



MODELS

Model	Part No.	Size	Capacity	Division
BSM3006	620164	300x300mm	6kg	1g
BSM3015	620165	300x300mm	15kg	2g
BSM3030	620166	300x300mm	30kg	5g
BSM3030L	620167	300x400mm	30kg	5g
BSM3060L	620168	300x400mm	60kg	10g
BSM3150L	620169	300x400mm	150kg	20g
BSM4030	620170	400x400mm	30kg	5g
BSM4060	620171	400x400mm	60kg	10g
BSM4150	620172	400x400mm	150kg	20g
BSM4060L	620173	400x500mm	60kg	10g
BSM4150L	620174	400x500mm	150kg	20g
BSM4200L	620175	400x500mm	200kg	50g
BSM5060	620176	500x600mm	60kg	10g
BSM5150	620177	500x600mm	150kg	20g
BSM5300	620178	500x600mm	300kg	50g
BSM6150	620179	600x600mm	150kg	20g
BSM6300	620180	600x600mm	300kg	50g
BSM6500	620181	600x600mm	500kg	100g

DIMENSION / mm

Model	a	b	h	h1	pack size	G.W/kg	1PC/CTN
BSM3*	300	300	120	350	695*415*160	11	1
BSM3*L	300	400	120	450	795*415*160	13	1
BSM4*	400	400	145	450	795*515*160	15	1
BSM4*L	400	500	145	550	895*515*160	18	1
BSM5*	500	600	155	650	996*615*175	25	1
BSM6*	600	600	155	650	995*715*175	30	1

